

HYDRON INCORPORATED

HYDRAULIC CHIPPERS & DIGGERS

STANLEY[®]

CH15 Chipping Hammer DR19 Digger

Stanley's CH15 Chipping Hammer is ideal for light demolition such as curbing or vault work and the DR19 Digger is ideal for trench digging or loosening hard earth. Both tools are small and compact making them good choices for work in confined areas. The CH15 and DR19 use common hex steel bits.



CH15



DR19

SPECIFICATIONS

| No. | Weight | Length | Width | Flow Range | Pressure | Blows/Minute | Capacity |
|-----------|--------|--------|-------|------------|---------------|--------------|----------------------|
| CH1513101 | 16 lbs | 17 in. | 3 in. | 7-9 gpm | 1000-2000 psi | 1800 bpm | .580 Hex |
| CH1553101 | 16 lbs | 17 in. | 3 in. | 4-6 gpm | 1000-2000 psi | 1800 bpm | .580 Hex |
| DR19111 | 22 lbs | 20 in. | 3 in. | 7-9 gpm | 1500-2000 psi | 1800 bpm | 3 1/4 x 7/8 in. Shnk |

HYDRAULIC
TOOLS &
ACCESSORIES

HYDRAULIC BREAKERS

Light Duty 45 Pound Class

45 pound class breaker models represent the lighter end of Stanley's broad selection of breakers. 45 pound class breakers are used for light to medium concrete demolition, asphalt cutting, steel or aluminum post driving, ground rod driving, and hard packed earth digging. Models available with standard or anti-vibration handles. All models accept standard breaker steels.



BR45



BR45S



BR72



BR72S

Medium Duty 75 Pound Class

75 pound class breakers are the worker's favorites. These breakers are just right for most construction workers and can perform much of the work that larger air breakers are used for. They are used for medium to heavy concrete demolition and asphalt cutting. Models in this class are available with standard or anti-vibration handles. All models accept standard breaker steels.

Heavy Duty 90 Pound Class

90 pound class breaker models are the workhorses of Stanley's selection of over 35 breaker models. These rugged breakers are highly productive in utility construction, street maintenance, and general contracting jobs. All models accept standard breaker steels.



BR89

SPECIFICATIONS

| No. | Weight | Length | Width | Flow Range | Pressure | Blows/Minute | Capacity | Misc. |
|----------|--------|--------|-----------|------------|---------------|--------------|-------------------|----------------|
| BR45120E | 56 lbs | 25 in. | 14 in. | 7-9 gpm | 1500-2000 psi | 1800 bpm | 6 x 1-1/8 in Hex | EZ Ride Ft |
| BR45125S | 58 lbs | 28 in. | 17.5 in. | 7-9 gpm | 1500-2000 psi | 1800 bpm | 6 x 1-1/8 in Hex | Anti Vibration |
| BR72120 | 59 lbs | 28 in. | 14.25 in. | 7-9 gpm | 1500-2000 psi | 1700 bpm | 6 x 1-1/8 in. Hex | T Handle |
| BR72125S | 61 lbs | 29 in. | 17.5 in. | 7-9 gpm | 1500-2000 psi | 1700 bpm | 6 x 1-1/8 in. Hex | Anti-Vibration |
| BR89120 | 83 lbs | 29 in. | 16 in. | 7-9 gpm | 1500-2000 psi | 1000 bpm | 6 x 1-1/8 in. Hex | T Handle |

320 Libbey Industrial Parkway, Weymouth, Massachusetts 02189
Phone 781-331-5500 • Fax 781-331-5508 • www.hydroninc.com