

# HYDRON INCORPORATED

## HYDRAULIC CUT-OFF SAWS & GRINDERS



Stanley's line of cut-off saws and grinders accommodate almost any kind of cutting or grinding work from concrete or metal cutting to deburring and shaping to underwater cutting. All tools accept commonly available abrasive carbide and diamond, cutting and grinding accessories.



**GR31 Grinder**



**C025 Cut-off Saw**



**C025 w/optional Saw Cart  
(No. 33281)**

### SPECIFICATIONS

No.	Weight	Length	Width	Flow Range	Pressure	Rotation/RPM	Wheel Capacity
CO25141	20 lbs	21 in.	11 in.	7-9 gpm	1500-2000 psi	CCW/4500	14 in. --
CO25541	20 lbs	21 in.	11 in.	7-9 gpm	1500-2000 psi	CW/4500	14 in.
GR31101	12 lbs	8 in.	28 in.	7-9 gpm	1500-2000 psi	CCW/5800	9 in.

## HYDRAULIC DIAMOND CHAIN SAWS

Stanley's diamond chain saws are light-weight and powerful and ideal for fast cutting of concrete, reinforced concrete, conduit, brick and other masonry. Plunge cutting is no problem. If you're involved in construction, remodeling, demolition, rescue, or water or sewer maintenance, you need one of these tools. Sealed saw chain requires less water pressure, from as low as 20 psi to 40-60 psi normally available from building water supply systems.



**DS06**



**DS11**

\*Bar and Chain Not Included, see page 103.

### SPECIFICATIONS

No.	Weight	Length	Width	Flow Range	Pressure	Cutting Capacity
DS063000	14 lbs	24 in.	9 in.	7-9 gpm	1000-2000 psi	8 in.
DS113000	26 lbs	38 in.	9 in.	7-9 gpm	1000-2000 psi	12, 15 in.

## HYDRAULIC HAMMER & SINKER DRILLS

Wood or steel drilling, concrete core or hold drilling, or blast holes is no problem with Stanley's complete line of drills. Also take a look at Stanley's impact wrenches for drilling in wood utility poles and large timbers.

### SPECIFICATIONS


No.	Weight	Length	Width	Flow Range	Pressure	Performance	Capacity	Misc.
HD08531G	6 lbs	13 in.	5-1/2 in.	3-9 gpm	750-2000 psi	1175 rpm @ 6 gpm	SDS Shk Plus	
HD45110B	45 lbs	22 in.	14 in.	7-9 gpm	1500-2000 psi	300 rpm	#736 Skil Hex	--
SK47130	52 lbs	23 in.	14 in.	7-9 gpm	1500-2000 psi	10 ft. Hole	7/8 in.x4-1/4 in. Hex Shank	Air Flush
CD10100	18 lbs	19 in.	4 in.	5-13 gpm	1000-2000 psi	380, 900 & 1800rpm	5/8 to 6 3/8 in. bits	Threaded



**HD08 Hammer Drill**



**CD10 Core Drill**



**HD45 Hammer Drill**



**SK47 Sinker Drill**

320 Libbey Industrial Parkway, Weymouth, Massachusetts 02189  
Phone 781-331-5500 • Fax 781-331-5508 • www.hydrone.com