

HYDRON INCORPORATED

CHAIN SLINGS

SINGLE CHAIN SLINGS



Chain Size (in.)	Rated Capacity Vertical (lbs.)		Approx. Weight 5 ft. Reach Type SOS (lbs.)
	Grade 80	Grade 100	
7/32	2,100	2,700	4
9/32	3,500	4,300	5
3/8	7,100	8,800	10
1/2	12,000	15,000	18




CO
Oblong Link

How to Order Chain Slings

Specify:

1. Grade 80 or Grade 100
2. Chain size - inches
3. Number of legs -
Single - (S)
4. Master Link- Oblong (O)
5. Bottom Attachments -
Oblong Link (CO)
6. Length of Assembly - feet
(Bearing point to bearing point)

WIRE ROPE SLINGS



Eye & Eye

WRC (Independent Wire Rope Core)

6x19 IWRC	Rope Dia. (in.)	IWRC			Min. Sling Length	Standard Eye Size (in.) W x L
		Rated Capacity (tons)				
		Vertical	Choker	Vertical Basket		
	1/4	.65	.48	1.3	1'6"	2 x 4
	5/16	1.0	.74	2.0	1'9"	2 1/2 x 5
	3/8	1.4	1.1	2.9	2'0"	3 x 6
	7/16	1.9	1.4	3.9	2'3"	3 1/2 x 7
	1/2	2.5	1.9	5.1	2'6"	4 x 8

How to Order Wire Rope Slings

Specify:

1. Rope Diameter - inches
2. Sling Length - feet (Bearing point to bearing point)
3. Description of rope construction class - 6 x 19 IWRC
4. Attachments - Eye & Eye

320 Libbey Industrial Parkway, Weymouth, Massachusetts 02189
Phone 781-331-5500 • Fax 781-331-5508 • www.hydrone.com