



HYDRON INCORPORATED

HOT MAXIMUM METERS

- Hot Maximum Meters are designed to retain the maximum current flow on energized conductors within $\pm 10\%$ of full scale reading.
- Maximum Meters can be installed with shotgun sticks.
- Ideal for locating faulted sections of overhead and underground circuits.
- Can be used for balancing conductor loads on multiple phase lines.
- Weatherproof — Meters are hermetically sealed.
- Maximum Meters can be used on all voltages and are reset with a magnet.
- Can be installed on conductors with a maximum diameter of 1-3/8".

| No. | Description | Scale Amps | Wt. |
|-------|------------------------------------|------------|-----|
| 11511 | Single Maximum Meter | 0-200 | 0.5 |
| 11241 | Single Maximum Meter | 0-500 | 0.5 |
| 11512 | Case of 3 Maximum Meters w/ magnet | 0-200 | 3.2 |
| 11240 | Case of 3 Maximum Meters w/ magnet | 0-500 | 3.2 |
| 12005 | Magnet only | | 0.3 |



Universal Installing Tool

- Universal installing tool can be used with Tel-O-Poles and maximum meters installed and removed without climbing the structure.

| No. | Wt. |
|--------|-----|
| 10-141 | .05 |



FAULT INDICATORS

- Fault Indicators are used to detect fault locations on overhead distribution systems.
- Four Trip Ratings available
- Bright red indicator for easy visual sighting.
- Installation - Indicators can be installed with conventional shotgun sticks or No. 10-141 installing tool (see above).
- Weatherproof - Fault Indicators are hermetically sealed.
- Indicators can be used on all primary voltages and are reset with magnet.
- Conductor Range - Indicators can be installed on conductors up to 1-1/2" max. diameter.
- Accuracy - $\pm 10\%$ of trip rating.

| No. | Description | Trip Rating | Wt. |
|--------|---|-------------|---------|
| 21361 | Single 100 Amp Fault Indicator | 100 Amps | 0.5 lbs |
| 21358 | Single 200 Amp Fault Indicator | 200 Amps | 0.5 lbs |
| 21359 | Single 450 Amp Fault Indicator | 450 Amps | 0.5 lbs |
| 21360 | Single 800 Amp Fault Indicator | 800 Amps | 0.5 lbs |
| P30306 | Carrying Case - holds 6 indicators and Reset magnet | | 1.7 lbs |
| 12005 | Manual Reset Magnet Only | | 0.3 lbs |



21358



P30306

TESTERS & LIVE
LINE TOOLS

320 Libbey Industrial Parkway, Weymouth, Massachusetts 02189
Phone 781-331-5500 • Fax 781-331-5508 • www.hydroninc.com