HYDRON INCORPORATED

FUSE PULLER

White safety line
The White Rubber Corporation

Has 1 1/4″ diameter fiberglass handle. The standard fuse puller heads (No. 92Q) have plastic jaws that fit fuses from 3/4″ to 2″ diameter. Heads are pivotally mounted to permit adjustment to any angle. To tighten the jaws, just rotate the handle. The insert jaws (No. 190NLF) for the 13/16″ diameter liquid filled fuse are held on the fuse puller with springs. The attachment on the end of each fuse puller is No. 190Q, quick change switch hook. Other lengths available. Bag not included.

190Q **196FGQ** **92Q**

NO.	DESCRIPTION	HANDLE LENGTH	WEIGHT
196FGU	Universal	6′6″	5 lbs
198FGU	Universal	8′	6 lbs
PARTS			
445578	Head Only, Universal		2 lbs
190NLF	Insert Jaws for 13/16″ diameter S&C Liquid Fuse		1 lb
BAGS			
B1	Protective Bag for 196FG		2 lbs
B101	Protective Bag for 198FG		2 lbs.

INSULATING LINK STICKS

NO.	OVERALL LENGTH IN	LENGTH BETWEEN FERRULES IN	FIBERGLASS DIAMETER IN	SWL LBS	WT. LBS	BAG NO.	WT. LB
50006EH	16″	6″	1″	2,500	2	**B516**	1
50012EH	22″	12″	1″	2,500	3	**B522**	1
50006EP	16″	6″	1″	2,500	2	**B516**	1
50012EP	22″	12″	1″	2,500	3	**B522**	1
5012EH	22″	12″	1 1/4″	2,500	2	**B522**	1
5018EH	28″	18″	1 1/4″	2,500	2	**B528**	1
5024EH	34″	24″	1 1/4″	2,500	3	**B534**	1
5012	22″	12″	1 1/4″	1,500	2	**B522**	1
5018	28″	18″	1 1/4″	1,500	2	**B528**	1
5024	34″	24″	1 1/4″	1,500	3	**B534**	1
5012R	22″	12″	1 1/4″	1,500	2	**B522**	1
5018R	28″	18″	1 1/4″	1,500	2	**B528**	1
5024R	34″	24″	1 1/4″	1,500	3	**B534**	1
5112	24″	12″	1 1/2″	2,500	2	**B522**	1
5118	30″	18″	1 1/2″	2,500	2	**B528**	1
5124	36″	24″	1 1/2″	2,500	3	**B534**	1
2512	28″	12″	1″	10,000	2	**B522**	1
2518	34″	18″	1″	10,000	2	**B528**	1
2524	40″	24″	1″	10,000	3	**B534**	1

Designed to isolate rope, hoists, and blocks being used between energized conductors and a pulling device. Also provide dielectric properties if strap hoist becomes contaminated through field use. Nos. 2512, 2518, and 2524 are made with solid fiberglass. All insulating link sticks are proof tested and marked with SWL prior to shipment. Other lengths and configurations available. All bags hold 3 link sticks. Bags not included. **FIBERGLASS TESTED AT 100 KV PER FOOT FOR 5 MINUTES.**

5012

5012R

5012EH

5112

2512

320 Libbey Industrial Parkway, Weymouth, Massachusetts 02189
Phone 781-331-5500 • Fax 781-331-5508 • www.hydroninc.com