


HYDRON INCORPORATED



CLIMBING/FALL
PROTECTION
EQUIPMENT & PPE

CARABINERS



5005SA Auto Lock Aluminum Carabiner

Length – 4 1/2"
Opening – 3/4"
Breaking Strength – 6700 lbs.



1710 Auto Lock Aluminum Carabiner

Length – 5 1/2"
Opening – 3/4"
Breaking Strength – 7000 lbs.



5005SAE Auto Lock Aluminum Carabiner with eye (Option U)

Length – 5 1/4"
Opening – .71"
Breaking Strength – 5620 lbs.



5005 Auto Lock Steel Carabiner

Length – 4 1/2"
Opening – 1"
Breaking Strength – 10,116 lbs.



***5005M Screw Gate Steel Carabiner**

Length – 4 1/2"
Opening – 1"
Breaking Strength – 11,240 lbs.



***5005T Twist Lock Steel Carabiner**

Length – 4 1/4"
Opening – 1"
Breaking Strength – 8,992 lbs.



5555SA Ball Lock Aluminum Carabiner

Length – 4 1/4"
Opening – .91"
Breaking Strength – 6295 lbs.



5555WSA William Ball Lock Aluminum Carabiner

Length – 4 1/2"
Opening – 1"
Breaking Strength – 5625 lbs.



***5005NA Non-Locking Aluminum Carabiner**

Length – 4 1/2"
Opening – 1 3/16"
Breaking Strength – 5000 lbs.



***5005NIA Non-Locking Aluminum Carabiner**

Length – 4"
Opening – .78"
Breaking Strength – 5172 lbs.



***5005NK Non-Locking Key Chain Carabiner**

Length – 3"
Opening – 1/2"
Breaking Strength – Not Rated

***WARNING:** Not intended for human support or fall protection.

320 Libbey Industrial Parkway, Weymouth, Massachusetts 02189
Phone 781-331-5500 • Fax 781-331-5508 • www.hydroninc.com